



The XTL 1e, 26° is designed with the latest LED and driver technology, inclosed in a rugged marine grade anodized aluminum housing and fitted with a AISI 316 stainless steel bracket.

The luminaire is equipped with high efficacy LEDs, for maximum light output with minimum heat generation, which make it possible to create a durable, stylish, minimalistic design, ensuring a long lasting product.

The luminaire can be implemented in all sorts of environments and industries, such as marine & offshore -, road -, agriculture -, architectural -and building sites, to mention a few.

Custom Kelvin, CRI and light color are available on request.

This variant of our XTL 1e floodlight is engineered for targeted illumination tasks requiring a narrow beam spread. Featuring precision-molded 26° optics, it delivers concentrated light output ideal for sign lighting, facade highlights, and directional spotlighting.

## TECHNICAL SPECIFICATIONS

<b>Wattage:</b>	11W
<b>Voltage:</b>	12-36 VDC
<b>Beam angle:</b>	26°
<b>LED Lifetime:</b>	100.000 Hours
<b>Kelvin:</b>	4000
<b>Lumen:</b>	1180
<b>CRI:</b>	90
<b>Dimensions:</b>	100 x 120 x 60 mm
<b>IP rating:</b>	IP67
<b>Warranty:</b>	5 years
<b>Temp. range:</b>	- 35°C → 50°C
<b>Weight:</b>	950 g
<b>Gland:</b>	M16 x 1.5
<b>Cabling:</b>	2000mm, H07RN-F, 2x1mm <sup>2</sup>

**Optional:** Other cabling can be included as per request

Technical specifications are calculated on data available from component manufacturers. Lumen/CRI/ Kelvin are calculated before optical transmission.

26.11.2025